

**Speed Prep Cleaner**

# 45 330SP

Proper substrate preparation plays an important role for the success of a paint job. Surface contamination is the most common reason for premature coating failures.

Speed Prep Cleaner has been specifically designed to remove waxes, grease, silicones, and other contaminants from bare metal and therefore eliminate avoidable adhesion problems.



## Directions for Use

**Preparation:**

- Pre-clean surface with a mild detergent and water when necessary.
- Surfaces must be dry before the application of 45 330SP
- Apply a generous amount of 45 330SP Speed Prep Cleaner to a clean cloth.
- Wipe surfaces to be cleaned before and after sanding.
- Wipe surfaces in one direction only, to eliminate smearing of contaminants.
- **Be sure to change rags frequently.**
- For maximum results, wipe dry with clean white cloths in one direction only, while the surface is still wet.
- **Never let the cleaner dry on the surface.**
- Blow off and tack surface prior to painting.

**Caution:**

**Refer to MSDS for appropriate solvent resistant gloves, respirator, and safety glasses while using 45 330SP Speed Prep Cleaner.**

**Do not use this product on fiberglass or plastic parts. Application on these surfaces can generate static build-up, which can result in a flash fire.**

**Technical Data:**

**Performance Characteristics**

Type	Solvent
Color	Clear
Usage	Metal surfaces
Speed of Evaporation	Medium
VOC	6.37 lbs./gal.
Flashpoint ( <i>Tag closed cup</i> )	60°F (16°C)

# 45 330SP

---

**Important:**

Before opening this package, be sure you understand the warning messages on the labels of all components, since the mixture will have the hazards of all its parts. Improper spray technique may result in a hazardous condition. Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

---

**See Material Safety Data Sheet and Labels for additional safety information and handling instructions.**

---

EMERGENCY MEDICAL OR SPILL CONTROL INFORMATION - US (412) 434-4515; CANADA (514) 645-1320; MEXICO 01-800-00-21-400

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public. Products mentioned may be hazardous and should only be used according to directions, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to Matthews Paint. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does Matthews Paint warrant freedom from patent infringement in the use of any formula or process set forth herein. If you require technical assistance, please call us toll-free 800/323-6593.



**MATTHEWS PAINT**

*The World's Finest Coating For Architectural Signage*

760 Pittsburgh Drive  
Delaware, OH 43015  
Toll Free: 800/323-6593  
Toll Free FAX: 800/947-0377